

TRUTEK TCTW i TCTB – CABLE TIES

Application:

- fastening all types of cabling
- fastening plastic pipes and corrugated pipes
- fixing cable installations in cars

Advantages:

- popular , simple and quick attachment
- rounded band edges facilitate assembly and exclude the possibility of injury
- low coefficient of drag when pulling cables through cable ties
- high quality band material - polyamide 6.6
- material of bands resistant to oils, greases, some acids and UV rays (black bands)
- band usage temperature from -40°C to +85°C
- band melting temperature from -10°C to +60°C
- maximum short-term temperature +110°C
- band melting point +256°C



Technical parameters of TCTW and TCTB cable ties *

Product Code (natural color)	Product Code (black colour)	Length L [mm]	Width W [mm]	Diameter E [mm]	Tensile strength [N]	Tensile strength [kg]
TCTW20075	TCTB22075	75	2.0	0,75-15	60	6,12
TCTW25098	TCTB25098	98	2.5	1,0-21	80	8,16
TCTW25135	TCTB25135	135	2.5	1,0-32	80	8,16
TCTW25160	TCTB26160	160	2.5	1,0-40	80	8,16
TCTW25200	TCTB26200	200	2.5	1,0-52	80	8,16
TCTW35140	TCTB36140	140	3.5	2,0-35	130	13,26
TCTW35200	TCTB36200	200	3.5	2,0-50	130	13,26
TCTW35290	TCTB36290	290	3.5	2,0-80	130	13,26
TCTW45160	TCTB45160	160	4.5	2,5-40	220	22,44
TCTW45178	TCTB48178	178	4.5	2,0-45	220	22,44
TCTW45200	TCTB48200	200	4.5	3,0-50	220	22,44
TCTW45250	TCTB48250	250	4.5	3,0-68	220	22,44
TCTW45290	TCTB48290	290	4.5	3,5-78	220	22,44
TCTW45360	TCTB48360	360	4.5	3,5-100	220	22,44
TCTW45430	TCTB48430	430	4.5	3,5-115	220	22,44
TCTW75180	TCTB78180	180	7.5	3,5-45	550	55,08
TCTW75240	TCTB78240	240	7.5	3,5-63	550	55,08
TCTW75300	TCTB78300	300	7.5	3,5-80	550	55,08
TCTW75365	TCTB78365	365	7.5	3,5-100	550	55,08
TCTW75450	TCTB78450	450	7.5	3,5-130	550	55,08
TCTW75540	TCTB78540	540	7.5	3,5-158	550	55,08
TCTW75750	TCTB78750	750	7.5	3,5-220	550	55,08

* special bands with increased resistance to UV rays, high or low temperature, dynamic loads, acids and bases are available on request

