



TRUTEK™
CONSTRUCTION FASTENING SYSTEMS

PRODUCT CATALOGUE 2024





CERTIFICATE

PCC-CERT

confirms, that:

Trutek Fasteners Polska Sp. z o. o.
ul. Wojska Polskiego 3, 39-300 Mielec

applies to the Integrated Management System and fulfills requirements of:

PN-EN ISO 9001:2015
PN-EN ISO 14001:2015


in scope of:

sales of assembly and anchoring systems for construction and industry.

Date of the certification decision: 22.02.2024
Certificate validity: 22.02.2024-21.02.2027
Certificate registration No.: PW-06002-24

PCC Manager

Mirosław Błaż



AC 082

Kobierzyce, 03.06.2024

The certificate remains valid upon fulfilling requirements of contract agreement No. 743/2023
PCC-CERT Group Sp. z o.o. ul. Sportowa 29, 55-040 Kobierzyce

ABOUT TRUTEK	4
PRODUCT SELECTOR	5
GAS & PAT TECHNOLOGY	6 - 10
MECHANICAL ANCHORS	11 - 18
CHEMICAL & ACCESSORIES	20 - 26
LIGHTWEIGHT ANCHORS	27 - 33
MASONARY NAILS	34
CABLE TIES	35
INSULATION ANCHORS	36- 38
CARBIDE DRILLING	39 - 40
ABRASIVE & DIAMOND DISCS	41
DRYWALL SCREWS	42 - 43
PHOTO VOLTAIC FIXINGS	44 - 45
TESTING EQUIPMENT	46 - 47
TRUTEK IPT POWER TOOLS	48 - 49
TRUTEK BRANDING	50

WHO ARE WE?

Trutek Fasteners is a part of an international holding group that includes production and trading companies operating in all parts of the world. Its distribution activity in Europe began in the United Kingdom in January 2002. Our company specialises in the production of top quality fastening systems for construction and industry. In our wide range, you will find both traditional products, used for many years in construction industry, and innovative, technologically advanced solutions that guarantee the highest level of safety, as well as easy and prompt application.

TOP QUALITY OF PRODUCTS - TECHNICAL APPROVALS, CERTIFICATES AND TESTS

Our products are subject to strict and demanding quality control that ensures the highest quality of the products and complete safety of their use. This is confirmed by numerous certificates and technical approvals.

FAST AND COMPLETE DELIVERIES

- Stock on hand. Advanced SAP computer system enables us to manage warehouse stock accurately and prevent product shortage.
- Prompt order execution. Orders from our Customers, regardless of the way of their submission, are immediately passed on for execution, so we guarantee delivery within 24 hours from ordering.
- Complete delivery information. The integration of our computer system with the shipment system of the forwarding company makes it possible to track the process of shipment online and predict the time of delivery.
- Delivery completeness. The process of the execution of orders involves checking mechanisms that provide multi-level inspection of delivery completeness, thus limiting possible mistakes.

TRAINING

Comprehensive program of trainings for our Commercial Partners is aimed to the best preparation of their personnel to serve Customers from the construction industry. The training program includes the following issues:

- Product training - it gives the opportunity to get fully familiar with our products, their technical characteristics and application in construction side conditions.
- Technical training - it includes expertise in the range of materials science, physical and chemical processes that occur during anchoring and product documentation required on construction sites, such as technical approvals, certificates and declarations of conformity.

TECHNICAL ASSISTANCE, ADVISING ON CONSTRUCTION SITES


Technical assistance is provided by a group of experts whose mission is to support design engineers and constructors in cases of innovative and difficult construction projects, as well as the optimum and complex choice of fastenings for typical applications that are common for constructions sites:

- telephone info-line technical support,
- choice of fastenings for a given project,
- anchors choice reports,
- materials for design engineers,
- anchors choice program,
- construction site test and presentations

ORDER PORTAL - ONLINE ORDERING

This is easy and fast way for purchasing at any time of the day and night. All the orders placed on the Internet retain all commercial conditions, and the interactive interface of information exchange gives the opportunity to agree non-standard conditions of product delivery.

- information on the availability of product of interest,
- information on the order value,
- information on the order processing progress;
- invoice prior to product delivery,
- special offers for web portal users,
- historical data review,
- waybill number, enabling the Customer to track the process of goods delivery





- Full Application
- Limited Use
- ◆ Technical approval

Product

11	HD - Heavy Duty Anchors
12 - 13	TX and TT - Throughbolts
14 - 15	TAB - Concrete Bolts
16	TS - Sleeve Anchors
17	TSA - Shield Anchors
18	TDA - Drop-In Anchors

20 - 23	TCM - Chemical Cartridge Anchors
24	TCS - Chemical Capsule Anchors

27	TNP - Nylon Plugs
27	THS - Nylon Hammerscrews
28	TSRB Scaffold Bolts
29	TSF - Sanitary Fixings
29	TNFA - Nylon Frame Long expansion
30	TNFAM - Multi Expansion Frame Anchor
31	TFCS - Door/Window Frame Screw
31	TKS - Tapscrew
32	TZH Zamac Hammer-In Anchor
32	TMH - All Steel Hammer-In Anchor
32	TME - Aerated Concrete express
32	TWH - Wirehangers
33	TDPA - Metal Plasterboard Anchor
33	TNPA - Nylon Plasterboard Anchor
33	TMS - All Purpose Screw Multifix
33	THW - Hollow Wall Anchors

BASE MATERIAL								FASTENING TYPE						
Concrete	Stone/Rock	Brickwork (Solid)	Brickwork (Perforated)	Hollow Block	Aerated Concrete Block	Plasterboard	Steel	Wood	Torque Controlled	Hammerset	Chemical	Others	ITB Approval	ETA Approval
■	■								✓					◆
■	■								✓				◆	◆
■	■											✓		◆
■	■	■							✓				◆	
■	■	■		■								✓	◆	◆
■	■									✓			◆	◆
■	■	■	■	■	●					✓			◆	◆
■	■	●								✓				◆
■	■	■	●	●	●				✓					
■	■	■	●	●	●					✓				
■	■	■	■	●	●				✓			✓		
■	■	■	■	●	●				✓					◆
■	■	■	■	■	●							✓		
■	■	■										✓		
■	■	■										✓		
■	■	■								✓				
■	■	■	●	●						✓				
■	■	■		●		■						✓		
■	■				■							✓		
■	■				■	■						✓		
■	■	■		●	●	■						✓		
			■			■						✓		

5



GAS NAILER TGT C38

(TOOL SUPPLIED COMPLETE IN A PACKING CASE)



Product Code	Energy Level (J)	Magazine Capacity (pcs)	Nail Length (mm)	Tool Weight (kg)	Gas Capacity	Battery Life
TGT C38	90	30 or 40	13 - 40	3.9	1200 shots	4000 shots

NEW


Premium Magazine Nails for Gas Nailer

For Fixing in Concrete

Product Code	Base Material	Nail Diameter (mm)	Nail Length (mm)	For use with	Box Packing	Outer Packing
TSGT19	Concrete	2.7	19	TGT C38	1000	5000
TSGT22	Concrete	2.7	22	TGT C38	1000	5000
TSGT25	Concrete	2.7	25	TGT C38	1000	5000
TSGT32	Concrete	2.7	32	TGT C38	1000	5000
TSGT38	Concrete	2.7	38	TGT C38	1000	5000



Super Premium Magazine Nails for For Gas Nailer

For Fixing in Steel

Product Code	Base Material	Nail Diameter (mm)	Nail Length (mm)	For use with	Box Packing	Outer Packing
TSGT17+	Steel	2.9/2.65	17	TGT C38	1000	5000
TSGT19+	Steel	2.9/2.65	19	TGT C38	1000	5000
TSGT22+	Steel	2.9/2.65	22	TGT C38	1000	5000



Premium Magazine Nails for For Gas Nailer C5 (fixing in concrete and Steel)

Product Code	Base Material	Nail Diameter (mm)	Nail Length (mm)	For use with	Box Packing	Outer Packing
TGT17C	Steel	3.0/2.6	17	DeWalt C5	800	4000
TGT19C	Steel	3.0/2.6	19	DeWalt C5	800	4000
TGT22C	Concrete	3.0/2.6	22	DeWalt C5	800	4000
TGT27C	Concrete	3.0/2.6	27	DeWalt C5	800	4000
TGT32C	Concrete	3.0/2.6	32	DeWalt C5	800	4000
TGT38C	Concrete	3.0/2.6	38	DeWalt C5	800	4000



Steel washer & Magnet for Gas Nailer

Product Code	Description	Washer Diameter (mm)	Box Packing	Outer Packing
TGA825MW	Steel washer for Gas Tool	25	200	3600
TGT100-104	Magnet for Gas Tool	25	-	-

Gas for Nail Guns

Product Code	Description	Fuel Cell Capacity (ml)	Weight of Fuel Cell (g)	For use with	Box Packing	Outer Packing
TGC165S	Gas for Gas Tools/Standard	80	40	C38/IS200	20	100





GAS NAILER TGT IS200

(TOOL SUPPLIED COMPLETE IN A PACKING CASE)



Product Code	Energy Level (J)	Magazine Capacity (pcs)	Insulation Thickness (mm)	Tool Weight (kg)	Gas Capacity	Battery Life
TGT IS200	90	-	25 - 200	3.3	800 shots	4000 shots

Insulation Anchor for Styrofoam & hard Rockwool (60 mm collar)

Product Code	Type of Substrate Material	Insulation Thickness (mm)	Nail Length	Box Packing	Outer Packing
TIF60050	Concrete	50	52	500	16000
TIF60060	Concrete	60	52	500	16000
TIF60070	Concrete	70	52	500	16000
TIF60080	Concrete	80	52	500	16 000
TIF60100	Concrete	100	52	450	14 400
TIF60120	Concrete	120	52	400	12 800
TIF60140	Concrete	140	52	300	9 600
TIF60150	Concrete	150	52	300	9 600
TIF60160	Concrete	160	52	250	8 000
TIF60180	Concrete	180	52	250	8 000
TIF60200	Concrete	200	52	200	6 400

Suitable for: Trutek TGT IS200 and LV600M



Insulation Anchor for soft Rockwool Fixing (90 mm collar)

Product Code	Type of Substrate Material	Insulation Thickness (mm)	Nail Length	Box Packing	Outer Packing
TIF90080	Concrete	80	52	250	8 000
TIF90100	Concrete	100	52	250	8 000
TIF90120	Concrete	120	52	200	6 400
TIF90140	Concrete	140	52	200	6 400
TIF90150	Concrete	150	52	150	4 800
TIF90160	Concrete	160	52	150	4 800
TIF90180	Concrete	180	52	100	3 200
TIF90200	Concrete	200	52	100	3 200

Suitable for: Trutek TGT IS200



NEW

POWDER ACTUATED TOOLS



Product Code	Cartridge Calibre	Head Diameter (mm)	Tool Weight (kg)	Magazine Nail Length/ Single (mm)	Tool Length
LV350	6.8/11 (Strip)	8	2,35	- / 16-62	340
LV500M	6.8/11 (Strip)	8	3.2	16-72 / 16-62	450
LV500 IS**	6.8/11 (Strip)	8	3.2	Insulation anchors up to 120mm	450

**Also available with adaptor to shoot up to 200mm



Suitable for: LV350, DX5 and DX4₆₀

Magazine cartridges - Calibre 6.8/11 mm

Product Code	Cartridge Calibre	Colour	Power of Cartridge	Box Packing	Outer Packing
TCGM	6.8/11	Green	Weak	100	10000
TCYM	6.8/11	Yellow	Average	100	10000
TCRM	6.8/11	Red	Strong	100	10000
TCBM	6.8/11	Black	Very Strong	100	10000



TDM Magazine Drive Pins

Product Code	Nail Diameter (mm)	Nail Length (mm)	Type of Substrate	Box Packing	Outer Packing
TDM16K	3.8	16	Steel	100	2000
TDM19K	3.8	19	Steel	100	2000
TDM22K	3.8	22	Steel	100	2000
TDM27	3.8	27	Concrete	100	2000
TDM32	3.8	32	Concrete	100	2000
TDM37	3.8	37	Concrete	100	2000
TDM42	3.8	42	Concrete	100	2000
TDM47	3.8	47	Concrete	100	2000
TDM52	3.8	52	Concrete	100	1000
TDM57	3.8	57	Concrete	100	1000
TDM62	3.8	62	Concrete	100	1000
TDM72	3.8	72	Concrete	100	1000

Suitable for: LV500M, DX5 and DX460

TDM Magazine Drive Pins - Premium Pin For Steel

Product Code	Nail Diameter (mm)	Nail Length (mm)	Type of Substrate	Box Packing	Outer Packing
TDM27+	3.8	27	Steel	100	2000
TDM32+	3.8	32	Steel	100	2000



TD Drive Pins 8/9 mm Plastic Washer

Product Code	Nail Diameter (mm)	Nail Length (mm)	Type of Substrate	Box Packing	Outer Packing
TD16K	3.8	16	Steel	100	2000
TD19K	3.8	19	Steel	100	2000
TD22K	3.8	22	Steel	100	2000
TD27	3.8	27	Concrete	100	2000
TD32	3.8	32	Concrete	100	2000
TD37	3.8	37	Concrete	100	2000
TD42	3.8	42	Concrete	100	2000
TD47	3.8	47	Concrete	100	2000
TD52	3.8	52	Concrete	100	1000
TD57	3.8	57	Concrete	100	1000
TD62	3.8	62	Concrete	100	1000
TD72	3.8	72	Concrete	100	1000
TD82	3.8	82	Concrete	100	1000
TD97	3.8	97	Concrete	100	1000
TH19**	3.8	19	Steel	100	5000

** Top Hat Pin for metal sheet fastening

Suitable for: LV350, DX5 and DX460



GAS & PAT TECHNOLOGY

TD Drive Pins 23 mm Metal Washer

Product Code	Nail Diameter (mm)	Nail Length (mm)	Type of Substrate	Washer Diameter (mm)	Box Packing	Outer Packing
TMWP27	3.8	27	Concrete	23	100	1500
TMWP32	3.8	32	Concrete	23	100	1500
TMWP47	3.8	47	Concrete	23	100	1500

Suitable for: LV350, DX5 and DX460



TD Framing Nail with Plastic Washer

Product Code	Head/Nail Diameter (mm)	Nail Length (mm)	Type of Substrate	Box Packing	Outer Packing
TDF47	8/3.8	47	Concrete	100	2000
TDF54	8/3.8	54	Concrete	100	2000
TDF62	8/3.8	62	Concrete	100	2000



TXCC Ceiling Anchor

(Suspension Clip suitable for 8mm Cartridge Tools)

Product Code	Shank Diameter (mm)	Nail Length (mm)	Box Packing	Outer Packing
TXCC32	3.8	32	100	2000

Suitable for: LV350, DX5 and DX460



TCC Conduit Clips

(Conduit Clip suitable for 8mm Cartridge Tools or TGTC38 Gas tool)

Product Code	Pipe/Cable Diameter (mm)	Hole Diameter (mm)	Box Packing	Outer Packing
TCC16	16	6	50	1000
TCC20	20	6	50	1000

Suitable for: LV350, LV600, TGTC38



LV600M



Product Code	Cartridge Calibre	Head Diameter (mm)	Tool Weight (kg)	Magazine Nail Length/ Single (mm)	Tool Length
LV600M	6.3/10 (Disk)	9	3.2	16-62 / 16-72	460



Product Code	Description
LV6005	Rubber Spring (damper for use with LV 600)
LV60020M9	Kit (magazine + nail guide) - 9mm (9mm barrel suitable for SPIT nails)
LV60017	Pin guide set for Insulation Anchors



TC...M Magazine Nails - (9mm Hd)

Product Code	Head/Nail Diameter (mm)	Nail Length (mm)	Type of Substrate	Box Packing	Outer Packing
TC15M	9/3.7	15	Steel	500	2500
TC20M	9/3.7	20	Concrete	500	2500
TC25M	9/3.7	25	Concrete	500	2500
TC30M	9/3.7	30	Concrete	500	2500
TC35M	9/3.7	35	Concrete	500	2500
TC40M	9/3.7	40	Concrete	300	1500
TC50M	9/3.7	50	Concrete	300	1500
TC60M	9/3.7	60	Concrete	300	1500



Suitable for: Trutek LV600M, SPIT P370



TC Nails with Plastic Washer - (9mm Hd)

Product Code	Head/Nail Diameter (mm)	Nail Length (mm)	Type of Substrate	Box Packing	Outer Packing
TC15	9/3.7	15	Steel	100	2000
TC20	9/3.7	20	Concrete	100	2000
TC25	9/3.7	25	Concrete	100	2000
TC30	9/3.7	30	Concrete	100	2000
TC35	9/3.7	35	Concrete	100	2000
TC40	9/3.7	40	Concrete	100	2000
TC50	9/3.7	50	Concrete	100	2000
TC60	9/3.7	60	Concrete	100	1000
TC70	9/3.7	70	Concrete	100	1000
TC80	9/3.7	80	Concrete	100	1000
TC90	9/3.7	90	Concrete	100	1000



Suitable for: Trutek LV600M, SPIT P370



Magazine Cartridges - Disk - Calibre 6.3/10 mm

Product Code	Cartridge Calibre	Colour	Power of Cartridge	Box Packing	Outer Packing
TDL10CG	6.3/10	Green	Medium	100	10000
TDL10CY	6.3/10	Yellow	Strong	100	10000
TDL10CR	6.3/10	Red	Very strong	100	10000



Suitable for: TRUTEK LV600M, SPIT P370



HDLM Anchor for Extreme Heavy Loads - Bolt (Steel White Zinc Plated)

Product Code	Drill Hole Diameter (mm)	Anchor Length (mm)	Max. Fixture Thickness (mm)	Min. Hole Depth (mm)	Box Packing
HDLM 10/10	10	75	10	65	50
HDLM 10/30	10	95	30	65	50
HDLM 10/50	10	115	50	65	50
HDLM 12/10	12	87	10	80	50
HDLM 12/30	12	107	30	80	50
HDLM 12/50	12	127	50	80	25
HDLM 15/15	15	108	15	95	25
HDLM 15/25	15	118	25	95	25
HDLM 15/45	15	138	45	95	25
HDLM 18/10	18	117	10	105	20
HDLM 18/20	18	127	20	105	20
HDLM 18/40	18	147	40	105	20
HDLM 24/20	24	152	20	130	10
HDLM 24/50	24	182	50	130	10
HDLM 28/10**	28	172	10	160	10
HDLM 28/30**	28	192	30	160	10
HDLM 28/60**	28	222	60	160	5



**Available on Request.

HDPM Anchor for Extreme Heavy Loads - Nut (Steel White Zinc Plated)

Product Code	Drill Hole Diameter (mm)	Anchor Length (mm)	Max. Fixture Thickness (mm)	Min. Hole Depth (mm)	Box Packing
HDPM 10/10	10	77	10	65	50
HDPM 10/30	10	97	30	65	50
HDPM 10/50	10	117	50	65	50
HDPM 12/10	12	90	10	80	50
HDPM 12/30	12	110	30	80	50
HDPM 12/50	12	130	50	80	25
HDPM 15/15	15	111	15	95	25
HDPM 15/25	15	121	25	95	25
HDPM 15/45	15	141	45	95	25
HDPM 18/10	18	122	10	105	20
HDPM 18/20	18	132	20	105	20
HDPM 18/40	18	152	40	105	20
HDPM 24/20	24	157	20	130	10
HDPM 24/50	24	187	50	130	10
HDPM 28/10	28	181	10	160	10
HDPM 28/30	28	201	30	160	10
HDPM 28/60	28	231	60	160	5



Extreme Heavy Loads HDF Anchor - Countersunk Head (Steel White Zinc Plated)

Product Code	Drill Hole Diameter (mm)	Anchor Length (mm)	Max. Fixture Thickness (mm)	Min. Hole Depth (mm)	Box Packing
HDF12/10**	12	80	10	80	50
HDF12/25**	12	95	25	80	50
HDF15/10**	15	95	10	95	25
HDF15/25**	15	110	25	95	25
HDF18/20**	18	115	20	105	20
HDF18/40**	18	135	40	105	20

**Available on Request.





Throughbolt Anchor ETA Option 1 – Crack Approved (Steel White Zinc Plated, St/St Clip)

Product Code	Drill Hole Diameter (mm)	Anchor Length (mm)	Max. Fixture Thickness (mm)	Min. Hole Depth (mm)	Box Packing	Outer Packing
TX08060**	8	60	5	45	100	400
TX08075	8	75	10	55	100	400
TX08095	8	95	30	55	100	400
TX08115	8	115	50	55	50	200
TX10085	10	85	15	60	50	200
TX10105	10	105	35	60	50	200
TX10120	10	120	50	60	50	200
TX10140	10	140	70	60	50	200
TX12090**	12	90	15	60	50	200
TX12100	12	100	5	80	50	200
TX12125	12	125	30	80	50	200
TX12140	12	140	45	80	25	100
TX12175	12	175	80	80	25	100
TX16115**	16	115	15	80	25	100
TX16150	16	150	30	100	25	100

** Not included in the ETA approval



Throughbolt Anchor ETA Option 1 – Crack Approved (Stainless Steel A4-316)

Product Code	Drill Hole Diameter (mm)	Anchor Length (mm)	Max. Fixture Thickness (mm)	Min. Hole Depth (mm)	Box Packing
TX08075SS	8	75	10	45	100
TX08085SS	8	85	20	55	100
TX08095SS	8	95	30	55	100
TX08115SS	8	115	50	55	50
TX10090SS	10	90	20	60	50
TX10105SS	10	105	35	60	50
TX10120SS	10	120	50	60	50
TX12090SS**	12	90	15	60	50
TX12100SS	12	100	5	80	50
TX12110SS	12	110	15	80	50
TX12125SS	12	125	30	80	50
TX12140SS	12	140	45	80	25
TX16090SS**	16	90	-	80	25
TX16115SS**	16	115	15	80	25
TX16145SS	16	145	25	100	25
TX16175SS	16	175	55	100	25

** Not included in the ETA approval



Throughbolt Anchor ETA Option 7 – Non Crack Approved (Stainless Steel A4-316)

Product Code	Drill Hole Diameter (mm)	Anchor Length (mm)	Max. Fixture Thickness (mm)	Min. Hole Depth (mm)	Box Packing
TTM08060SS	8	60	-	-	100
TTM08075SS	8	75	10	65	100
TTM08095SS	8	95	30	65	100
TTM08120SS	8	120	55	65	100
TTM10060SS	10	60	-	-	50
TTM10090SS	10	90	15	70	50
TTM10105SS	10	105	30	70	50
TTM10120SS	10	120	45	70	50
TTM10145SS	10	145	70	70	50
TTM10175SS	10	175	100	70	50
TTM12075SS	12	75	-	-	25
TTM12095SS	12	95	-	-	25
TTM12110SS	12	110	15	90	25
TTM12125SS	12	125	30	90	25
TTM12145SS	12	145	50	90	25
TTM12160SS	12	160	65	90	25
TTM12180SS	12	180	85	90	25
TTM16115SS	16	115	-	-	20
TTM16130SS	16	130	10	110	20
TTM16150SS	16	150	30	110	20
TTM16180SS	16	180	60	110	20
TTM16200SS	16	200	80	110	10

**M6 & M20 and other lengths also available



Throughbolt Anchor ETA Option 7 - Non Crack Approved
(Steel Hot Dipped Galvanized)

Product Code	Drill Hole Diameter (mm)	Anchor Length (mm)	Max. Fixture Thickness (mm)	Min. Hole Depth (mm)	Box Packing	Outer Packing
TT08050G**	8	50	-	50	200	800
TT08060G	8	60	5	50	100	400
TT08080G	8	80	25	50	100	400
TT08090G	8	90	35	50	100	400
TT08115G	8	115	60	50	100	400
TT10065G	10	65	5	55	100	400
TT10090G	10	90	30	55	50	200
TT10105G	10	105	45	55	50	200
TT10120G	10	120	60	55	50	200
TT10140G	10	140	80	55	50	200
TT12080G	12	80	5	70	50	200
TT12100G	12	100	25	70	50	200
TT12120G	12	120	45	70	25	100
TT12140G	12	140	65	70	25	100
TT12180G	12	180	105	70	25	100
TT16105G	16	105	5	90	25	100
TT16125G	16	125	15	90	20	80
TT16150G	16	150	50	90	20	80



MECHANICAL ANCHORS

Throughbolt Anchor ETA Option 7 - Non Crack Approved
(Steel White Zinc Plated)

Product Code	Drill Hole Diameter (mm)	Anchor Length (mm)	Max. Fixture Thickness (mm)	Min. Hole Depth (mm)	Box Packing	Outer Packing
TT06045**	6	45	-	35	250	1000
TT06055**	6	55	-	35	250	1000
TT06085**	6	85	32	35	200	800
TT08050**	8	50	1	43	200	800
TT08065	8	65	10	43	100	400
TT08080	8	80	25	43	100	400
TT08090	8	90	35	43	100	400
TT08100	8	100	45	43	100	400
TT08115	8	115	60	43	100	400
TT08130	8	130	75	43	50	200
TT10065**	10	65	1	48	100	400
TT10075	10	75	10	48	100	400
TT10090	10	90	25	48	50	200
TT10105	10	105	40	48	50	200
TT10120	10	120	55	48	50	200
TT10140	10	140	75	48	50	200
TT12080	12	80	1	60	50	200
TT12100	12	100	20	60	50	200
TT12120	12	120	40	60	25	100
TT12140	12	140	60	60	25	100
TT12180	12	180	100	60	25	100
TT12200	12	200	120	60	25	100
TT12220	12	220	140	60	15	60
TT12240	12	240	160	60	10	40
TT16105	16	105	1	70	25	100
TT16125	16	125	20	70	20	80
TT16150	16	150	45	70	20	80
TT16175	16	175	70	70	20	80
TT16200	16	200	95	70	20	80
TT16220	16	220	115	70	15	60
TT16240	16	240	135	70	10	40
TT20130	20	130	5	90	15	60
TT20160	20	160	35	90	10	40
TT20220	20	220	95	90	10	40
TT20240	20	240	115	90	5	20
TT24180**	24	180	30	110	10	40
TT24260**	24	260	110	110	5	20



UKTA-23/6667



** Non ETA products, ITB certification only.

NEW


Anchor Bolt for Concrete

Hex Flange Head Option 1 - Crack Approval

(steel white zinc plated)

No expansion/No Stress

No expansions stress with mechanical interlock between base material and anchor.



Product Code	Drill Hole Diameter (mm)	Anchor Thread Diameter (mm)	Anchor Length (mm)	Max.Fixture Thickness (mm)	Minimum Embedment Depth (mm)	Min.Hole Depth (mm)	Hex Head Dia A/F (mm)	Box Packaging
TUS06050	6	8	50	20	30	40	10	100
TUS06075	6	8	75	45	30	40	10	100
TUS06100	6	8	100	70	30	40	10	100
TUS06130	6	8	130	100	30	40	10	100
TUS06150	6	8	150	120	30	40	10	100
TUS08060	8	10	60	20	40	50	12	100
TUS08075	8	10	75	35	40	50	12	50
TUS08100	8	10	100	60	40	50	12	50
TUS10060	10	12	60	10	50	60	14	50
TUS10075	10	12	75	25	50	60	14	50
TUS10100	10	12	100	50	50	60	14	50
TUS10125	10	12	125	75	50	60	14	50
TUS10140	10	12	140	90	50	60	14	25
TUS10150	10	12	150	100	50	60	14	25
TUS12075	12	14	75	20	55	70	17	50
TUS12100	12	14	100	45	55	70	17	25
TUS12120	12	14	120	65	55	70	17	25
TUS12130	12	14	130	75	55	70	17	25
TUS12150	12	14	150	95	55	70	17	25
TUS14100	14	16	100	45	55	70	20	10
TUS14120	14	16	120	65	55	70	20	10
TUS14130	14	16	130	75	55	70	20	10
TUS14150	14	16	150	95	55	70	20	10

Also Available in Countersunk and Pan Head



Anchor Bolt for Concrete - Rod Hanger (Steel white zinc plated)

Product Code	Drill Hole Diameter (mm)	Anchor Thread Diameter (mm)	Anchor Length (mm)	Inner Thread Diameter (mm)	Min.Hole Depth (mm)	Hex Head Dia A/F (mm)	Box Packaging
TAB6/35/8-10RH	6	7.5	35	8/10	30	13	100
TAB6/55/8-10RH	6	7.5	55	8/10	50	13	100



MECHANICAL ANCHORS

Anchor Bolt for Concrete - Hex Flange Head ETA OPTION 7 - Non Crack Approved

Product Code	Drill Hole Diameter (mm)	Anchor Thread Diameter (mm)	Anchor Length (mm)	Max.Fixture Thickness (mm)	Hex Head Dia A/F (mm)	Box Packaging
TAB06050F*	6	8	50	20	10	100
TAB06075F*	6	8	75	45	10	100
TAB06100F*	6	8	100	70	10	100
TAB06130F*	6	8	130	100	10	100
TAB06150F*	6	8	150	120	10	100
TAB08060F	8	10	60	20	12	100
TAB08075F	8	10	75	35	12	50
TAB08100F	8	10	100	60	12	50
TAB10060F	10	12	60	10	14	50
TAB10075F	10	12	75	25	14	50
TAB10100F	10	12	100	50	14	50
TAB10125F	10	12	125	75	14	50
TAB10140F	10	12	140	90	14	25
TAB10150F	10	12	150	100	14	25
TAB12075F	12	14	75	20	17	50
TAB12100F	12	14	100	45	17	25
TAB12120F	12	14	120	65	17	25
TAB12130F	12	14	130	75	17	25
TAB12150F	12	14	150	95	17	25



** Non ETA products



Sleeve Anchor - Hex Nut (Steel White Zinc Plated)

Product Code	Drill Hole Diameter (mm)	Anchor Length (mm)	Max. Fixture Thickness (mm)	Min. Hole Depth (mm)	Box Packing	Outer Packing
TS06026	6	26	5	25	100	1200
TS06040	6	40	8	30	100	1200
TS06060	6	60	28	30	100	1200
TS08040	8	40	8	40	100	1200
TS08065	8	65	30	40	50	600
TS08090	8	90	55	40	50	600
TS10040	10	40	6	40	50	600
TS10050	10	50	10	45	50	600
TS10075	10	75	35	45	50	400
TS10100	10	100	60	45	50	400
TS10125	10	125	85	45	50	400
TS12060	12	60	15	55	50	300
TS12075	12	75	20	55	50	300
TS12100	12	100	50	55	25	200
TS12125	12	125	75	55	25	200
TS16065	16	65	15	60	25	125
TS16110	16	110	55	60	10	50
TS16145	16	145	85	60	10	50
TS20080	20	80	20	65	10	50
TS20115	20	115	55	65	10	50
TS20160	20	160	100	65	10	50



Sleeve Anchor - Hex Bolt - 5.8 grade (Steel White Zinc Plated)

Product Code	Drill Hole Diameter (mm)	Anchor Length (mm)	Max. Fixture Thickness (mm)	Min. Hole Depth (mm)	Box Packing	Outer Packing
TS08045H	8	45	8	40	100	1200
TS08070H	8	70	30	40	50	600
TS08090H	8	90	50	40	50	600
TS10055H	10	55	10	45	50	600
TS10080H	10	80	35	45	50	400
TS10100H	10	100	60	45	50	400
TS12065H	12	65	1	55	50	300
TS12080H	12	80	25	60	50	300
TS12100H	12	100	45	60	20	160
TS16075H	16	75	15	60	25	125
TS16110H	16	110	55	65	10	50



Sleeve Anchor - Hook and Eye Bolts (Steel White Zinc Plated)

Product Code	Drill Hole Diameter (mm)	Inner Diameter (mm)	Type of Head	Min. Hole Depth (mm)	Box Packing	Outer Packing
TS 08045X	8	8	Eyelet	45	100	800
TS 08045K	8	11	Hook	45	100	800



(Steel White Zinc Plated)

R120 – 120 min fire resistance



(Steel White Zinc Plated)

R120 – 120 min fire resistance

(Steel White Zinc Plated)

(Steel White Zinc Plated)



NEW

Also Available in A2 Stainless



Drop-in Anchor - Lipped

(Steel White Zinc Plated)

Product Code	Thread Diameter (mm)	Drill Hole Diameter (mm)	Anchor Length (mm)	Min. Hole Depth (mm)	Box Packing	Outer Packing
TDA08L	8	10	30	33	100	2000
TDA10LS	10	12	30	33	50	1000
TDA10L	10	12	40	43	50	1000
TDA12L	12	16	50	54	50	500
TDA16L	16	20	65	70	25	200

Drop-in Anchor - Short Lipped

TDA08SH	10	12	25	28	50	2000
TDA10SH	12	16	25	28	50	1000
TDA12SH	16	20	25	28	25	500



Drop-in Anchor - Non Lipped

(Steel White Zinc Plated)

Product Code	Thread Diameter (mm)	Drill Hole Diameter (mm)	Anchor Length (mm)	Min. Hole Depth (mm)	Box Packing	Outer Packing
TDA06	6	8	25	25	100	2000
TDA08	8	10	30	33	100	2000
TDA10	10	12	40	43	50	1000
TDA12	12	16	50	54	50	500
TDA16	16	20	65	70	25	200
TDA20	20	25	80	85	25	100

Drop-In Anchor

(Stainless Steel A4-316)

Product Code	Thread Diameter (mm)	Drill Hole Diameter (mm)	Anchor Length (mm)	Min. Hole Depth (mm)	Box Packing	Outer Packing
TDA06SS	6	8	25	25	100	2000
TDA08SS	8	10	30	30	100	2000
TDA10SS	10	12	40	40	50	1000
TDA12SS	12	16	50	50	50	500
TDA16SS	16	20	65	70	25	200



Drop-in Anchor - Knurled

(Steel White Zinc Plated)

Product Code	Thread Diameter (mm)	Drill Hole Diameter (mm)	Anchor Length (mm)	Min. Hole Depth (mm)	Box Packing	Outer Packing
TDK06	6	8	25	28	100	2000
TDK08	8	10	30	33	100	2000
TDK10	10	12	40	43	50	1000
TDK12	12	16	50	54	50	500
TDK16	16	20	65	70	25	200



Drop-In Anchor Setting Tool

Product Code	Sleeve Thread Diameter (mm)	For use with	Box Packing	Outer Packing
TDST06	6	TDA06, TDA06L, TDA06SS	1	—
TDST08	8	TDA08, TDA08L, TDA08SS	1	—
TDST10	10	TDA10, TDA10L, TDA10SS	1	—
TDST12	12	TDA12, TDA12L, TDA12SS	1	—
TDST16	16	TDA16, TDA16L, TDA16SS	1	—
TDST20	20	TDA20	1	—
Product Code	Description			Box Packing
TDST1025	M10 x 25 Soft Grip Setting Tool for Lipped Drop-In's			1
TDST1030	M10 x 30 Soft Grip Setting Tool for Lipped Drop-In's			1
TDST1250	M12 x 50 Soft Grip Setting Tool for Lipped Drop-In's			1





****Trutek Drop-In anchors must be installed using Trutek setting tools**

DesignFix®

THE BENCHMARK FOR ANCHOR DESIGN BECOME A REAL ANCHOR PROFESSIONAL

DesignFix is an all-purpose anchor design program for manufacturers of fasteners for free distribution to their clients such as engineers, planners or craftsmen. By using the software, the clients can design mechanical and chemical heavy duty anchors under static loads and under the influence of earthquake.



FOR MORE DETAILS PLEASE VISIT
WWW.TRUTEK.COM.PL

MEDIUM TO HEAVY LOADS

NEW


POLYESTER
UNIVERSAL 10:1

TCM 300/420 MS PRO - Polyester With Styrene

- Suitable for medium loads for non-critical applications.
- Fast working times for early loading in time sensitive applications.
- Use in damp & wet environments and fixing holes.
- Extremely versatile in masonry, hollow, aerated concrete.
- Crack and gap filling repairs in concrete vertical or horizontal.
- 10:1 Resin available in a variety of cartridge types.



Product Code	Recommended Type of Substrate	Capacity (ml)	Box Packaging	For Use with:
TCM300MS PRO	Concrete, Stone	300	12	TCM300MTP
TCM420MS PRO	Concrete, Stone	420	12	TCM420MTP



MEDIUM TO HEAVY LOADS



POLYESTER UNIVERSAL
STYRENE FREE 10:1

TCM 300/420 M PRO - Polyester Styrene Free

- Suitable for medium loads for non-critical applications.
- Fast working times for early loading in time sensitive applications.
- No styrene allows for use indoors and in enclosed spaces.
- Use in damp & wet environments and fixing holes.
- Extremely versatile in masonry, hollow, aerated concrete.
- Crack and gap filling repairs in concrete vertical or horizontal.
- 10:1 Resin available in a variety of cartridge types.



Product Code	Recommended Type of Substrate	Capacity (ml)	Box Packaging	For Use with:
TCM300M PRO	Concrete, Stone	300	12	TCM300MTP
TCM420M PRO	Concrete, Stone	420	12	TCM420MTP



Number of Fixings per Cartridge

Anchor Diameter (mm)	Drill Hole Diameter (mm)	Hole Depth (mm)	Resin Capacity/number of holes		
			420 ml	400 ml	300 ml
8	12	80	112	108	81
10	12	90	80	78	58
12	14	110	56	54	40
16	18	125	37	36	27
20	24	170	10	10	7
24	28	210	7	7	5
30	35	280	3,5	3	3



MEDIUM TO HEAVY LOADS



TCM 420 PRO + - Vinylster Styrene Free

- Suitable for high loads within standard annulus and embedments.
- Fast working times for early loading in time sensitive applications.
- No styrene allows for use indoors and in enclosed spaces.
- Use in wet or flooded environments and fixing holes.
- High durability, resistance to chemicals.
- Used for studs and rebar.
- 10:1 resin available in a variety of cartridge types.
- Fixings in concrete, wood, or other high strength material

Product Code	Recommended Type of Substrate	Capacity (ml)	Box Packaging	For Use with:
TCM300 PRO +	Concrete, Stone	300	12	TCM300MTP
TCM420 PRO +	Concrete, Stone	420	12	TCM420MTP



VINYLESTER
STYRENE FREE 10:1



MEDIUM TO HEAVY LOADS

TCM 300/420A - Arctic



- Suitable for medium loads for non-critical applications.
- Fast working times for early loading in time sensitive applications.
- Use in extremely cold environments and fixing holes.
- Extremely versatile in masonry, hollow, aerated concrete.
- Crack and gap filling repairs in concrete vertical or horizontal.
- 10:1 resin available in a variety of cartridge types

Product Code	Recommended Type of Substrate	Capacity (ml)	Box Packaging	For Use with:
TCM300 A	Concrete, Stone	300	12	TCM300MTP
TCM420 A	Concrete, Stone	420	12	TCM420MTP



ARCTIC EPOXY ACRYLATE
STYRENE FREE 10:1



- Arctic working temperature up to -18C

TCMFX Pure Epoxy



- Suitable for high loads featuring large diameters and deep embedment.
- Longer working times make it suitable for large holes, and high temperatures.
- No shrinkage, good for large diameter fixings.
- Use in wet or flooded environments and fixing holes, or underwater.
- High durability, resistance to chemicals.
- Used for diamond drilled holes.
- Solvent free resin.
- Fixings in concrete, wood, or other high strength materials.

Product Code	Recommended Type of Substrate	Capacity (ml)	Box Packaging	For Use with:
TCMFX	Concrete, Stone	585	10	TCM585MT



HEAVY LOADS



PURE EPOXY
STYRENE FREE



HEAVY LOADS



PURE EPOXY
STYRENE FREE

TCM 100 - Pure Epoxy 1:1

- Suitable for high loads featuring large diameters and deep embedments.
- Longer working times make it suitable for larger holes and high temperatures
- No shrinkage, good for large diameter
- Use in wet or flooded environments and fixing holes, or underwater.
- High durability, resistance to chemicals.
- Used for diamond drilled holes.
- Solvent free resin.
- Fixings in concrete, wood, or other high strength materials.



100 Year Anchor Service Life

Product Code	Recommended Type of Substrate	Capacity (ml)	Box Packaging	For Use with:
TCM100400	Concrete, Stone	400	10	TCM400MTP
TCM100600	Concrete, Stone	600	10	TCM600MTP



HEAVY LOADS



PURE EPOXY
STYRENE FREE

TCM 500 - Pure Epoxy 3:1

- Suitable for high loads featuring large diameters and deep embedments.
- Longer working times make it suitable for large holes, and high temperatures.
- No shrinkage, good for large diameter
- Use in wet or flooded environments and fixing holes, or underwater.
- High durability, resistance to chemicals.
- Used for diamond drilled holes.
- Solvent free resin.
- Fixings in concrete, wood, or other high strength materials.



100 Year Anchor Service Life

Product Code	Recommended Type of Substrate	Capacity (ml)	Box Packaging	For Use with:
TCM500385	Concrete, Stone	385	10	TCM385MT
TCM500585	Concrete, Stone	585	10	TCM585MT



DesignFiX®

Utilizing DesignFiX software in conjunction with Trutek's construction chemical mortar offers a host of advantages in the field of construction. The software, tailored to specific design requirements, ensures precise calculations and optimal material utilization, thereby enhancing the overall efficiency of construction projects.

Trutek's construction chemical mortar, known for its high-quality and durable composition, complements this process by providing a reliable bonding solution that enhances structural integrity. The seamless integration of DesignFiX software and Trutek's mortar not only streamlines the planning phase but also promotes cost-effectiveness and sustainability, as it minimizes waste and maximizes the performance of the construction materials. This synergy results in a construction process that is not only technologically advanced but also robust and environmentally conscious.

for more information on DesignFiX please contact us on below:

info@trutekfixings.co.uk



TCM300MTP - Resin Extusion Tool

Product Code	For Use with Cartridge capacity (ml)	Bag Packing	Carton Packing
TCM300MTP	All 300ml single cartridges	1	12



TCM420MTP - Resin Extusion Tool

Product Code	For Use with Cartridge capacity (ml)	Bag Packing	Carton Packing
TCM420MTP	All 420ml single cartridges	1	10



TCM400MTP - Resin Extusion Tool

Product Code	For Use with Cartridge capacity (ml)	Bag Packing	Carton Packing
TCM400MTP	All 400ml 1:1 (side by side) cartridges	1	5



TCM585MT - Resin Extusion Tool

Product Code	For Use with Cartridge capacity (ml)	Bag Packing	Carton Packing
TCM585MT	All 385+585ml 3:1 (side by side) cartridges	1	5



TCM101BTP - Battery Resin Extusion Tool

Product Code	For Use with Cartridge capacity (ml)	Box Contents
TCM101BTP	All 10:1 resin cartridges	2 x 4Ah Li Batteries and charger



TCM31BTP - Battery Resin Extusion Tool

Product Code	For Use with Cartridge capacity (ml)	Box Contents
TCM31BTP	All 3:1 resin cartridges	2 x 4Ah Li Batteries and charger



TCM11BTP - Battery Resin Extusion Tool

Product Code	For Use with Cartridge capacity (ml)	Box Contents
TCM11BTP	All 1:1 resin cartridges	2 x 4Ah Li Batteries and charger





Glass Spin-In Capsules Epoxy Acrylate ETA Option 7 – Non Crack Approved

Product Code	Drill Hole Diameter (mm)	Thread Diameter (mm)	Capsule Length (mm)	Min. Hole Depth (mm)	Box Packing	Outer Packing
TSC08	10	8	110	80	10	500
TSC10	12	10	130	90	10	500
TSC12	14	12	160	110	10	200
TSC16	18	16	190	125	10	200
TSC20	25	20	260	170	6	60
TSC24	28	24	300	210	6	60

Hammer-In Capsules available on request



Glass Spin-In Capsules Vinylester Styrene Free- ETA Option 1 – Crack Approved

Product Code	Drill Hole Diameter (mm)	Thread Diameter (mm)	Capsule Length (mm)	Min. Hole Depth (mm)	Box Packing	Outer Packing
TSC08V	10	9	85	85	10	500
TSC10V	12	11	85	85	10	500
TSC12V	14	13	95	110	10	500
TSC14V	16	15	98	120	10	500
TSC16V	18	17	98	125	10	500
TSC20V	24	22	175	180	6	120
TSC22V	26	22	185	190	6	120
TSC24V	28	24	210	210	6	126
TSC27V	32	27	250	265	2	28
TSC30V	35	30	265	280	2	28



Glass Hammer-In Capsules Vinylester

Product Code	Drill Hole Diameter (mm)	Thread Diameter (mm)	Capsule Length (mm)	Min. Hole Depth (mm)	Box Packing	Outer Packing
THC08V	10	9	85	85	10	500
THC10V	13	11	85	85	10	500
THC12V	15	13	95	110	10	500
THC14V	18	15	98	120	10	500
THC16V	20	17	98	125	10	500
THC20V	24	22	175	180	6	120
THC22V	26	22	185	190	6	120
THC24V	28	24	210	210	6	126
THC27V	32	27	250	265	2	28
THC30V	35	30	265	280	2	28



Chemical Stud Anchor with hexagon socket

(Steel White Zinc Plated)

Product Code	Drill Hole Diameter (mm)	Thread Diameter (mm)	Anchor Length (mm)	Max. Fixture Thickness (mm)	Min. Hole Depth (mm)	Box Packing	Outer Packing
TCS08110	10	8	110	18	80	10	200
TCS10130	12	10	130	25	90	10	200
TCS12160	14	12	160	34	110	10	80
TCS16190	18	16	190	45	125	10	80
TCS20260	25	20	260	55	170	10	30
TCS24300	28	24	300	55	210	5	30



Chemical Stud Anchor

(Steel Hot-dip Galvanized)

Product Code	Drill Hole Diameter (mm)	Thread Diameter (mm)	Anchor Length (mm)	Max. Fixture Thickness (mm)	Min. Hole Depth (mm)	Box Packing	Outer Packing
TCS08110G	10	8	110	18	80	10	200
TCS10130G	12	10	130	25	90	10	200
TCS12160G	14	12	160	34	110	10	90
TCS16190G	18	16	190	45	125	10	90
TCS20260G	25	20	260	55	170	10	40
TCS24300G	28	24	300	55	210	5	20



Chemical Stud Anchor - Hexagon

(Stainless Steel A4-316)

Product Code	Drill Hole Diameter (mm)	Thread Diameter (mm)	Anchor Length (mm)	Max. Fixture Thickness (mm)	Min. Hole Depth (mm)	Box Packing	Outer Packing
TCS08110SS-A4	10	8	110	18	80	10	-
TCS10130SS-A4	12	10	130	25	90	10	-
TCS12160SS-A4	14	12	160	34	110	10	-
TCS16190SS-A4	18	16	190	45	125	10	-
TCS20260SS-A4	25	20	260	55	170	10	-
TCS24300SS-A4	28	24	300	55	210	5	-
TCS30380SS-A4	35	30	380	70	280	5	-





Product Code	Drill Hole Diameter (mm)	Outer Diameter of Sleeve (mm)	For use with Threaded Rods	Sleeve Length (mm)	Box Packing
TMS12	12	12	M6-M8	1000	1
TMS16	16	16	M10-M12	1000	1
TMS22	22	20	M12-M16	1000	1
TMS26	26	24	M20	1000	1



Nylon Plug without collar (no screw)

Product Code	Drill Hole Diameter (mm)	Plug Length (mm)	Screw Diameter (mm)	Screw Gauge	Min.Hole Depth (mm)	Box Packing	Outer Packing
TNP05	5	25	2.5 - 4.0	4	30	200	7200
TNP06	6	30	3.5 - 5.0	6-10	35	200	7200
TNP07	7	35	4.0 - 5.5	8-12	40	200	3600
TNP08	8	40	5.0 - 6.0	10-14	45	200	3600
TNP10	10	50	6.0 - 8.0	14-18	55	100	1800
TNP12	12	60	8.0 - 10.0	18-24	65	50	1800
TNP14	14	75	10.0 - 12.0	24-32	80	50	1800



Nylon Plug with collar

TNP05C	5	30	2.5 - 4.0	4	30	200	7200
TNP06C	6	35	3.5 - 5.0	6-10	35	200	7200
TNP07C	7	40	4.0 - 5.5	8-12	40	200	3600
TNP08C	8	45	5.0 - 6.0	10-14	45	200	3600
TNP10C	10	55	6.0 - 8.0	14-18	55	100	1800
TNP12C	12	65	8.0 - 10.0	18-24	65	50	1800
TNP14C	14	80	10.0 - 12.0	24-32	80	50	1800



Nylon Hammerscrews Countersunk BZP

Product Code	Drill Hole Diameter (mm)	Plug Length (mm)	Max Fixture Thickness (mm)	Min.Hole Depth (mm)	Screw Dia/ Length (mm)	Box Packing	Outer Packing
THS05025	5	25	1	28	3.50/27	200	7200
THS05030	5	30	5	35	3.50/32	200	7200
THS05040	5	40	15	45	3.50/43	200	3600
THS05050	5	50	25	55	3.50/55	200	3600
THS06040	6	40	10	45	3.85/43	200	3600
THS06050	6	50	20	55	3.85/53	100	1800
THS06060	6	60	30	65	3.85/63	100	1800
THS06080	6	80	50	85	3.85/83	100	1800
THS08045	8	45	5	50	4.85/50	100	1800
THS08060	8	60	20	65	4.85/65	100	1800
THS08080	8	80	40	85	4.85/85	100	1200
THS08100	8	100	60	105	4.85/105	100	1200
THS08120	8	120	80	125	4.85/125	100	1200
THS08140	8	140	100	145	4.85/145	100	1200



Stainless Steel Hammerscrews available on request.

Nylon Hammerscrews BZP

Product Code	Drill Hole Diameter (mm)	Plug Length (mm)	Max Fixture Thickness (mm)	Min.Hole Depth (mm)	Screw Dia/ Length (mm)	Box Packing	Outer Packing
Mushroom Head							
THS06040M	6	40	10	45	3.85/43	200	3600
THS06060M	6	60	30	65	3.85/63	100	1800
THS06080M	6	80	50	85	3.85/83	100	1800
Round Flat Hea							
THS05025F	5	25	-	28	3.50/27	200	7200
THS05030F	5	30	5	35	3.50/32	200	7200
THS05040F	5	40	15	45	3.50/43	200	3600
THS05050F	5	50	25	55	3.50/55	200	3600
THS06040F	6	40	10	45	3.85/43	200	3600
THS06050F	6	50	20	55	3.85/53	100	1800
THS06060F	6	60	30	65	3.85/63	100	1800
THS06080F	6	80	50	85	3.85/83	100	1800
THS08045F	8	45	5	50	4.85/50	100	1800
THS08060F	8	60	20	65	4.85/65	100	1800
THS08080F	8	80	40	85	4.85/85	100	1200
THS08100F	8	100	60	105	4.85/105	100	1200
THS08120F	8	120	80	125	4.85/125	100	1200
THS08140F	8	140	100	145	4.85/145	100	1200



(Galvanised Steel)

Product Code	Anchor Diameter (mm)	Anchor Length (mm)	Thread Length (mm)	Eye Diameter (mm)	Working Length (mm)	Box Packing	Outer Packing
TSRB12090	12	90	65	23	15	25	-
TSRB12120	12	120	65	23	45	25	-
TSRB12160	12	160	65	23	85	25	-
TSRB12190	12	190	65	23	115	25	-
TSRB12230	12	230	65	23	155	10	-
TSRB12300	12	300	65	23	225	10	-
TSRB12350	12	350	65	23	275	10	-
TSRB12400	12	400	65	23	325	10	-
TSRB12450	12	450	65	23	375	10	-



Product Code	Anchor Diameter (mm)	Plug Length (mm)	Eye Diameter (mm)	Working Length (mm)	Box Packing	Outer Packing
TNP14075 L	14	75	23	-	50	1800
TNP14100 L	14	100	23	-	50	600
TNP14135 L	14	135	23	-	50	600
TNP14185 L	14	185	23	-	50	600



NEW

(Galvanised Steel)

Product Code	Anchor Diameter (mm)	Anchor Length (mm)	Thread Diameter (mm)	Eye Diameter (mm)	Hole Depth (mm)	Box Packing	Outer Packing
TSIB12215	18	215	12	50	130	25	-
TSIB12270	18	270	12	50	180	25	-
TSIB1290TS (Threaded Stud)	12	90	12	-	-	25	-
TSIB1254S (Spacer)	18	54	12	-	-	25	-
TSB1245W (Spacer)	18	45	-	-	-	100	-

TAM Anchors on Pg 17.



NEW

(Galvanised Steel)

Product Code	Anchor Diameter (mm)	Anchor Length (mm)	Thread Diameter (mm)	Eye Diameter (mm)	For Use with	Box Packing	Outer Packing
TSRB16	25	210	16	50	TDA16	5	40



Nylon Frame Anchors Long Expansion C/Sunk Head

Product Code	Drill Hole Diameter (mm)	Plug Length (mm)	Max Fixture Thickness (mm)	Min.Hole Depth (mm)	Screw Dia/Length (mm)	Box Packing	Outer Packing
TNFA08100LE	8	100	30	80	5.50/105	100	900
TNFA08120LE	8	120	50	80	5.50/125	100	900
TNFA10080LE	10	80	10	80	7.00/85	50	450
TNFA10100LE	10	100	30	80	7.00/105	50	450
TNFA10115LE	10	115	45	80	7.00/120	50	450
TNFA10135LE	10	135	65	80	7.00/140	50	450
TNFA10160LE	10	160	90	80	7.00/165	50	300



Nylon Frame Anchors Long Expansion Hex Head

Product Code	Drill Hole Diameter (mm)	Plug Length (mm)	Max Fixture Thickness (mm)	Min.Hole Depth (mm)	Screw Dia/Length (mm)	Box Packing	Outer Packing
TNFA10080LEH	10	80	10	80	7.00/85	50	450
TNFA10100LEH	10	100	30	80	7.00/105	50	450
TNFA10115LEH	10	115	45	80	7.00/120	50	450
TNFA10135LEH	10	135	65	80	7.00/140	50	450
TNFA10160LEH	10	160	90	80	7.00/165	50	300
TNFA10180LEH	10	180	110	80	7.00/185	50	300



Sanitary Fixings (BZP screw, WC fixing, White and Chrome)

Product Code	Drill Hole Diameter (mm)	Plug Length (mm)	Screw Length (mm)	Screw Diameter (mm)	Cap Diameter (mm)	Polybag Packing	Outer Packing
TSFT68010W	10	50	80	6	10	1	100
TSFT68010C	10	50	80	6	10	1	100



Sanitary Fixings (BZP screw, Basin fixing)

Product Code	Drill Hole Diameter (mm)	Plug Length (mm)	Screw Length (mm)	Screw Diameter (mm)	Screw Cap Diameter (mm)	Polybag Packing	Outer Packing
TSFB08100	12	60	100	8	40	1	100
TSFB08120	12	60	120	8	40	1	100
TSFB08140	12	60	140	8	40	1	100
TSFB10120	14	70	120	10	40	1	100
TSFB10140	14	70	140	10	40	1	100



Sanitary Fixings (BZP screw, Urinal fixing)

Product Code	Drill Hole Diameter (mm)	Plug Length (mm)	Screw Length (mm)	Screw Diameter (mm)	Cap Diameter (mm)	Polybag Packing	Outer Packing
TSFU08100	12	60	100	8	40	1	100
TSFU08120	12	60	120	8	40	1	100
TSFU08140	12	60	140	8	40	1	100
TSFU10120	14	70	120	10	40	1	100
TSFU10140	14	70	140	10	40	1	100



** Chrome Head also available

All Purpose Frame Anchors - MULTI EXPANSION - ETA Option 7 – Non Crack Approved

(nylon, countersunk flat head, zinc plated)



Ø 8mm socket PZ, Ø 10mm socket TORX40

Product Code	Drill Hole Diameter (mm)	Anchor Length (mm)	Max. Fixture Thickness (mm)	Min. Hole Depth (mm)	Screw Diameter (mm)	Screw Length (mm)	Box Packing	Outer Packing
TNFAM08080	8	80	10	70	5,5	85	100	600
TNFAM08100	8	100	30	70	5,5	105	100	600
TNFAM08120	8	120	50	70	5,5	125	100	600
TNFAM08140	8	140	70	70	5,5	145	100	600
TNFAM10080	10	80	10	70	7,0	85	50	400
TNFAM10100	10	100	30	70	7,0	105	50	400
TNFAM10120	10	120	50	70	7,0	125	50	400
TNFAM10140	10	140	70	70	7,0	145	25	200
TNFAM10160	10	160	90	70	7,0	165	25	200
TNFAM10200	10	200	130	70	7,0	205	25	200
TNFAM10230	10	230	160	70	7,0	237	20	180
TNFAM10260	10	260	190	70	7,0	265	20	180

All Purpose Frame Anchors - MULTI EXPANSION ETA Option 7 – Non Crack Approved

(nylon, hexagon head with washer, zinc plated)



Product Code	Drill Hole Diameter (mm)	Anchor Length (mm)	Max. Fixture Thickness (mm)	Min. Hole Depth (mm)	Screw Diameter (mm)	Screw Length (mm)	Box Packing	Outer Packing
TNFAM10080F	10	80	10	70	7,0	85	50	400
TNFAM10100F	10	100	30	70	7,0	105	50	400
TNFAM10120F	10	120	50	70	7,0	125	25	200
TNFAM10140F	10	140	70	70	7,0	145	25	200
TNFAM10160F	10	160	90	70	7,0	165	25	200

All Purpose Frame Anchors - MULTI EXPANSION - ETA Option 7 – Non Crack Approved

(nylon, hexagon head, zinc plated)



Product Code	Drill Hole Diameter (mm)	Anchor Length (mm)	Max. Fixture Thickness (mm)	Min. Hole Depth (mm)	Screw Diameter (mm)	Screw Length (mm)	Box Packing	Outer Packing
TNFAM10080H	10	80	10	70	7,0	85	50	400
TNFAM10100H	10	100	30	70	7,0	105	50	400
TNFAM10120H	10	120	50	70	7,0	125	50	400
TNFAM10140H	10	140	70	70	7,0	145	25	200
TNFAM10160H	10	160	90	70	7,0	165	25	250
TNFAM10200H	10	200	130	70	7,0	205	25	200
TNFAM10240H	10	240	170	70	7,0	245	20	180
TNFAM10260H	10	260	190	70	7,0	265	20	180

All Purpose Frame Anchors - MULTI EXPANSION - ETA Option 7 – Non Crack Approved

(nylon, countersunk flat head, stainless steel A4 (grade 316))



Product Code	Drill Hole Diameter (mm)	Anchor Length (mm)	Max. Fixture Thickness (mm)	Min. Hole Depth (mm)	Screw Diameter (mm)	Screw Length (mm)	Box Packing	Outer Packing
TNFAM10080SS**	10	80	10	70	7,0	85	50	400
TNFAM10100SS**	10	100	30	70	7,0	105	50	400
TNFAM10120SS**	10	120	50	70	7,0	125	50	400
TNFAM10140SS**	10	140	70	70	7,0	145	25	200
TNFAM10160SS**	10	160	90	70	7,0	165	25	200

**available upon request



Door / Window Frame Screw

(Steel White Zinc Plated)

Product Code	Screw Diameter (mm)	Screw Length (mm)	Max. Fixture Thickness (mm)	Drill Hole Diameter (mm)	Box Packing
TFC575050	7,5	50	15	6	100
TFC575060	7,5	60	25	6	100
TFC575070	7,5	70	35	6	100
TFC575080	7,5	80	45	6	100
TFC575090	7,5	90	55	6	100
TFC575100	7,5	100	65	6	100
TFC575110	7,5	110	75	6	100
TFC575120	7,5	120	85	6	100
TFC575130	7,5	130	95	6	100
TFC575150	7,5	150	115	6	100
TFC575180	7,5	180	145	6	100
TFC575200	7,5	200	165	6	100



LIGHTWEIGHT ANCHORS

Tapscrew Blue Countersunk Hd

Product Code	Drill Hole Dia (mm)	Screw Dia (mm)	Screw Length (mm)	Max.Fixture Thickness (mm)	Min Hole Depth (mm)	Drive	Box Packing
TKS05032C	4	5	32	7	35	PH2	100
TKS05045C	4	5	45	20	35	PH2	100
TKS05070C	4	5	70	45	35	PH2	100
TKS05082C	4	5	82	57	35	PH3	100
TKS06025C	5	6	25	7	35	PH3	100
TKS06045C	5	6	45	20	35	PH3	100
TKS06057C	5	6	57	32	35	PH3	100
TKS06070C	5	6	70	45	35	PH3	100
TKS06100C	5	6	100	75	35	PH3	100
TKS06125C	5	6	125	100	35	PH3	100



Tapscrew Blue Hex Hd

Product Code	Drill Hole Dia (mm)	Screw Dia (mm)	Screw Length (mm)	Max.Fixture Thickness (mm)	Min Hole Depth (mm)	Drive	Box Packing
TKS05032H	4	5	32	7	35	6.5	100
TKS05045H	4	5	45	20	35	6.5	100
TKS05057H	4	5	57	32	35	6.5	100
TKS06032H	5	6	32	7	35	8	100
TKS06045H	5	6	45	20	35	8	100
TKS06057H	5	6	57	32	35	8	100
TKS06070H	5	6	70	45	35	8	100
TKS06082H	5	6	82	57	35	8	100
TKS06100H	5	6	100	75	35	8	100





(ZnAl)						
Product Code	Hole Diameter (mm)	Anchor Length (mm)	Max. Fixture Thickness (mm)	Min. Hole Depth (mm)	Box Packing	Outer Packing
TZH06030	6	30	8	22	100	1600
TZH06040	6	4	18	22	100	1600
TZH06050	6	50	28	22	100	1600
TZH06065	6	65	43	22	50	800

Product Code	Hole Diameter (mm)	Anchor Length (mm)	Max. Fixture Thickness (mm)	Min. Hole Depth (mm)	Box Packing	Outer Packing
TMH06040	6	40	5	35	100	2000
TMH06070	6	70	30	40	100	1000

(Steel White Zinc Plated)						
Product Code	Hole Diameter (mm)	Anchor Length (mm)	Screw Diameter (mm)	Min. Hole Depth (mm)	Box Packing	Outer Packing
TME06032	7 - 9	32	3,5 - 4,0	38	200	3600
TME08038	10 - 12	38	3,5 - 4,0	46	100	1800
TME08060	10 - 12	60	4,5 - 5,0	68	100	900
TME10060	12 - 14	60	6,0 - 8,0	68	50	900

Product Code	Hole Diameter (mm)	Anchor Length (mm)	Max. Fixture Thickness (mm)	Min. Hole Depth (mm)	Box Packing	Outer Packing
TWH06055	6	55	-	40	100	2000

Product Code	Type	Hole Diameter (mm)	Anchor Diameter (mm)	Anchor Length (mm)	Max. Fixture Thickness (mm)	Box Packing
TM56532ZC	Round Head	5	6.5	29	12	100



Drywall Anchors (supplied with a screw)

Product Code	Screw Diameter (mm)	Screw Length (mm)	Max. Fixture Thickness (mm)	Anchor Length (mm)	Box Packing	Outer Packing
TDPA (Driva)	4	30	15	30	100	1000
TNPA38	4	38	15	45	100	1000



Super MAX Anchor (supplied with bolt)

Product Code	Drill Hole Diameter (mm)	Screw Length (mm)	Max. Board Thickness (mm)	Anchor Length (mm)	Box Packing	Outer Packing
TSM10	10	65	3-30	35	100	1000



Steel Drywall Anchor (Steel White Zinc Plated)

Product Code	Drill Hole Diameter (mm)	Anchor Length (mm)	Max. Fixture Thickness (mm)	Wall Thickness (mm)	Box Packing	Outer Packing
THW04025	8	25	8	0 - 5	200	3200
THW04045	8	45	16	8 - 16	100	1600
THW04050	8	50	17	16 - 23	100	1600
THW04065	8	65	20	18 - 32	100	1600
THW05045	10	45	17	6 - 13	100	1600
THW05060	10	60	26	8 - 16	100	1600
THW05070	10	70	30	16 - 32	100	800
THW06060	13	60	35	7 - 16	100	800
THW06070	13	70	30	16 - 32	100	800



THW Anchor Installation Tool

Product Code	Description	Box Packing
THWT01	Setting Tool for THW	1



Perforated Steel Straps

Product Code	Description	Tape Width (mm)	Tape Thickness (mm)	Tape Length (M)	Box Packing
TFP12	Steel mounting tape	12	0.7	10	10
TFP17	Steel mounting tape	17	0.7	10	10
TFP25	Steel mounting tape	25	0.7	10	5



Setting Pin & Tool

Product Code	Description	Pin Length (mm)	Pin Diameter (mm)	Collar Diameter (mm)	Box Packing
TSP18	Steel mounting tape	18	0.7	8	200
TSP22	Steel mounting tape	22	0.7	8	200
TSPT	Pin Setting Tool	-	-	-	1





Hardened Nails for Concrete and Brick (without washer)

Product Code	Nail Diameter (mm)	Nail Length (mm)	Box Packing	Outer Packing	Nail Weight 100pcs/kg
THMN25025W	2.5	25	100	15000	0,11
THMN25030W	2.5	30	100	15000	0,13
THMN25040W	2.5	40	100	9000	0,18
THMN25050W	2.5	50	100	7000	0,20
THMN25060W	2.5	60	100	5000	0,24
THMN30025W	3.0	25	100	15000	0,15
THMN30030W	3.0	30	100	15000	0,17
THMN30040W	3.0	40	100	9000	0,25
THMN30050W	3.0	50	100	7000	0,29
THMN30060W	3.0	60	100	5000	0,37
THMN35050W	3.5	50	100	5000	0,40
THMN35060W	3.5	60	100	5000	0,51
THMN35075W	3.5	75	100	5000	0,58
THMN35090W	3.5	90	100	2500	0,65
THMN35100W	3.5	100	100	2500	0,81



Hardened Nails for Concrete (knurled)

Product Code	Nail Diameter (mm)	Nail Length (mm)	Box Packing	Outer Packing	Nail Weight 100pcs/kg
THMN27020WK	2.7	20	250	12500	0,076
THMN27025WK	2.7	25	250	12500	0,094
THMN27030WK	2.7	30	250	12500	0,121
THMN27035WK	2.7	35	250	6250	0,132
THMN27040WK	2.7	40	250	6250	0,152
THMN27050WK	2.7	50	250	6250	0,190
THMN35035WK	3.5	35	250	6250	0,255
THMN35045WK	3.5	45	250	6250	0,327
THMN35050WK	3.5	50	250	6250	0,365
THMN35055WK	3.5	55	250	6250	0,401
THMN35065WK	3.5	65	250	6250	0,476
THMN35070WK	3.5	70	250	3000	0,512
THMN35075WK	3.5	75	250	3000	0,549
THMN35080WK	3.5	80	250	3000	0,584
THMN45030WK	4.5	30	250	3000	0,294
THMN45040WK	4.5	40	250	3000	0,392
THMN45050WK	4.5	50	250	3000	0,490
THMN45055WK	4.5	55	250	3000	0,533
THMN45060WK	4.5	60	250	3000	0,588
THMN45065WK	4.5	65	250	3000	0,636
THMN45070WK	4.5	70	250	3000	0,684
THMN45080WK	4.5	80	250	3000	0,781



Cable Ties

Product Code (Natural Colour)	Product Code (Colour Black)	Length (mm)	Width (mm)	Diameter (mm)	Box Packing	Outer Packing	Tensile Strength (kg)
TCTW20075	TCTB20075	75	2.0	0,75-15	100	60 000	6,12
TCTW25098	TCTB25098	98	2.5	1,0-21	100	40 000	8,16
TCTW25135	TCTB25135	135	2.5	1,0-32	100	35000	8,16
TCTW25160	TCTB25160	160	2.5	1,0-40	100	35000	8,16
TCTW25200	TCTB25200	200	2.5	1,0-52	100	25000	8,16
TCTW35140	TCTB35140	140	3.5	2,0-35	100	25000	13,26
TCTW35200	TCTB35200	200	3.5	2,0-50	100	20000	13,26
TCTW35290	TCTB35290	290	3.5	2,0-80	100	15000	13,26
TCTW45160	TCTB45160	160	4.5	2,5-40	100	15000	22,44
TCTW45178	TCTB45178	178	4.5	2,0-45	100	15000	22,44
TCTW45200	TCTB45200	200	4.5	3,0-50	100	13000	22,44
TCTW45250	TCTB45250	250	4.5	3,0-68	100	10000	22,44
TCTW45290	TCTB45290	290	4.5	3,5-78	100	10000	22,44
TCTW45360	TCTB45360	360	4.5	3,5-100	100	7500	22,44
TCTW45430	TCTB45430	430	4.5	3,5-115	100	6000	22,44
TCTW75180	TCTB75180	180	7.5	3,5-45	100	6000	55,08
TCTW75240	TCTB75240	240	7.5	3,5-63	100	5000	55,08
TCTW75300	TCTB75300	300	7.5	3,5-80	100	4000	55,08
TCTW75365	TCTB75365	365	7.5	3,5-100	100	3500	55,08
TCTW75450	TCTB75450	450	7.5	3,5-130	100	3000	55,08
TCTW75540	TCTB75540	540	7.5	3,5-158	100	2000	55,08
TCTW75750	TCTB75750	750	7.5	3,5-220	100	2000	55,08



CABLE TIES

Cable Tie Mounts

Product Code	Cable Tie Holder	Box Packing	Outer Packing
TGA8BBP	For use with Gas/PAT tools	100	1000



Cable Tie Pin Holders

Product Code	Hole Diameter (mm)	Min. Hole Depth (mm)	Sizes				Box Packing
			A [mm]	B [mm]	C [mm]	D [mm]	
TCTP08	8	50	10	37	6,5	9,7	100



Product Reference	Anchor Diameter (mm)	Anchor Length (mm)	Min. Hole Depth (mm)	Drill Diameter (mm)	Head/Disc Diameter (mm)	Carton Packing
TMIA08090	8	90	100	8	35	250
TMIA08110	8	110	120	8	35	250
TMIA08140	8	140	150	8	35	250
TMIA08170	8	170	180	8	35	250
TMIA08200	8	200	210	8	35	250
TMIA08250	8	250	260	8	35	125
TMIA08300	8	300	310	8	35	125
TMIA80W						

Product Reference	Anchor Diameter (mm)	Anchor Length (mm)	Min. Hole Depth (mm)	Drill Diameter (mm)	Head/Disc Diameter (mm)	Carton Packing
TMIA08090SS	8	90	100	8	35	250
TMIA08110SS	8	110	120	8	35	250
TMIA08140SS	8	140	150	8	35	250
TMIA08170SS	8	170	180	8	35	250
TMIA08200SS	8	200	210	8	35	250
TMIA08250SS	8	250	260	8	35	125
TMIA08300SS	8	300	310	8	35	125
TMIA80WSS						

Product Reference	Drill Hole Diameter (mm)	Anchor Length (mm)	Anchor Depth (mm)	Polybag Quantity	Outer Packing
TIA10080IENCC	10	80	50	100	1000
TIA10090IENCC	10	90	50	100	1000
TIA10100IENCC	10	100	50	100	1000
TIA10110IENCC	10	110	50	100	1000
TIA10120IENCC	10	120	50	100	1000
TIA10140IENCC	10	140	50	100	1000
TIA10160IENCC	10	160	50	100	1000
TIA10180IENCC	10	180	50	100	1000
TIA10200IENCC	10	200	50	100	1000
TIA10220IENCC	10	220	50	50	500

Product Reference	Drill Hole Diameter (mm)	Anchor Length (mm)	Anchor Depth (mm)	Polybag Quantity	Outer Packing
TIA10080IENWC	10	80	50	100	1000
TIA10090IENWC	10	90	50	100	1000
TIA10100IENWC	10	100	50	100	1000
TIA10110IENWC	10	110	50	100	1000
TIA10120IENWC	10	120	50	100	1000
TIA10140IENWC	10	140	50	100	1000
TIA10160IENWC	10	160	50	100	1000
TIA10180IENWC	10	180	50	100	1000
TIA10200IENWC	10	200	50	100	1000
TIA10220IENWC	10	220	50	50	500

Product Reference	Drill Hole Diameter (mm)	Anchor Length (mm)	Anchor Depth (mm)	Polybag Quantity	Outer Packing
TIA10140IENWP	10	140	80	200	-
TIA10160IENWP	10	160	80	200	-
TIA10180IENWP	10	180	80	200	-
TIA10200IENWP	10	200	80	200	-
TIA10220IENWP	10	220	80	100	-



Fixing into Concrete

Insulation Fixing - Short Expanding Zone

Insulation pin with Fibreglass expanding nail, 60mm Disc - White

Product Reference	Drill Hole Diameter (mm)	Anchor Length (mm)	Anchor Depth (mm)	Box Packing	Outer Packing
TIA10080FNWC	10	80	50	200	-
TIA10090FNWC	10	90	50	200	-
TIA10100FNWC	10	100	50	200	-
TIA10110FNWC	10	110	50	200	-
TIA10120FNWC	10	120	50	200	-
TIA10140FNWC	10	140	50	200	-
TIA10160FNWC	10	160	50	200	-
TIA10180FNWC	10	180	50	200	-
TIA10200FNWC	10	200	50	200	-
TIA10220FNWC	10	220	50	100	-



INSULATION ANCHORS

Fixing into Porotherm

Insulation Fixing - Long Expanding Zone

Insulation pin with Fibreglass expanding nail, 60mm Disc - White

Product Reference	Drill Hole Diameter (mm)	Anchor Length (mm)	Anchor Depth (mm)	Polybag Quantity	Outer Packing
TIA10140FNWP	10	140	80	200	-
TIA10160FNWP	10	160	80	200	-
TIA10180FNWP	10	180	80	200	-
TIA10200FNWP	10	200	80	200	-
TIA10220FNWP	10	220	80	100	-



Insulation Fixing - Flat Roofing

Insulation pin for flat Roofing with various screws

Product Reference	Drill Hole Diameter (mm)	Anchor Length (mm)	Head Diameter (mm)	Box Packing	Outer Packing
TIA14055FR	14	55	50	200	-
TIA14085FR	14	85	50	200	-
TIA14105FR	14	105	50	200	-
TIA14135FR	14	135	50	200	-
TIA14155FR	14	155	50	200	-
TIA14165FR	14	165	50	200	-
TIA14185FR	14	185	50	200	-
TIA14235FR	14	235	50	200	-
TIA14285FR	14	285	50	200	-
TIA14325FR	14	325	50	100	-



Various Screw types available



Polymide Insulation washer 90mm





Product Reference	Washer Diameter (mm)
TIA140	140



Polymide Insulation Anchor

Product Reference	Anchor Diameter (mm)	Anchor Length	Drive	Box Packing	Outer Packing
TIFD50	25	50	T40	50	600
TIFD90	25	90	T41	25	300







SDS Plus XTC 4 Cutter Drill Bits

Product Code	Drill Diameter (mm)	Working Length (mm)	Overall Length (mm)
TXTC05110	5	50	110
TXTC06110	6	50	110
TXTC07110	7	50	110
TXTC08110	8	50	110
TXTC05160	5	100	160
TXTC06160	6	100	160
TXTC08160	8	100	160
TXTC10160	10	100	160
TXTC12160	12	100	160
TXTC16160	16	100	160
TXTC06210	6	150	210
TXTC08210	8	150	210
TXTC10210	10	150	210

Product Code	Drill Diameter (mm)	Working Length (mm)	Overall Length (mm)
TXTC12210	12	150	210
TXTC16210	16	150	210
TXTC06260	6	200	260
TXTC65260	6.5	200	260
TXTC08260	8	200	260
TXTC10260	10	200	260
TXTC12260	12	200	260
TXTC14260	14	200	260
TXTC16260	16	200	260
TXTC08310	8	250	310
TXTC10310	10	250	310
TXTC12310	12	250	310
TXTC14310	14	250	310
TXTC16310	16	250	310



DRILLING

Kit of SDS Plus XTC 4 Cutter Drill Bits

Product Code	Drill Diameter (mm)	Working Length (mm)	Overall Length (mm)
P10TXTC05110	5	50	110
P10TXTC06110	6	50	110
P10TXTC07110	7	50	110
P10TXTC08110	8	50	110
P10TXTC05160	5	100	160
P10TXTC06160	6	100	160
P10TXTC08160	8	100	160

Product Code	Drill Diameter (mm)	Working Length (mm)	Overall Length (mm)
P10TXTC10160	10	100	160
P10TXTC12160	12	100	160
P10TXTC06210	6	150	210
P10TXTC08210	8	150	210
P10TXTC10210	10	150	210
P10TXTC12210	12	150	210

*The kit includes 10 drill bits.



SDS MAX Drill Bits

Product Code	Drill Diameter (mm)	Working Length (mm)	Overall Length (mm)
TCMU16690	16	550	690
TCMU16920	16	780	920
TCMU18690	18	550	690
TCMU18920	18	780	920
TCMU20690	20	550	690
TCMU20920	20	780	920
TCMU22340	22	200	340
TCMU22540	22	400	540
TCMU24340	24	200	340
TCMU24540	24	400	540
TCMU24690	24	550	690
TCMU25340	25	200	340
TCMU25540	25	400	540

Product Code	Drill Diameter (mm)	Working Length (mm)	Overall Length (mm)
TCMU26340	26	200	340
TCMU26540	26	400	540
TCMU28340	28	200	340
TCMU28690	28	550	690
TCMU28920	28	780	920
TCMU30540	30	400	540
TCMU32540	32	400	540
TCMU35540	35	400	540
TCMU36540	36	400	540
TCMU36920	36	780	920
TCMU38540	38	400	540
TCMU40690	40	550	690
TCMU40920	40	780	920
TCMU42690	42	550	690
TCMU42920	42	780	920





SDS-Plus Chisels

Product Code	Description/Dimensions (mm)	Overall Length (mm)
TPPC12250	Pointed Ø12x250	250
TPPC14250	Pointed Ø14x250	250
TPFC20250	Flat Chisel 20mm	250
TPFC40250	Flat Chisel 40mm	200
TCPC22250	Concrete Chasing 22mm	250
TPAB40200	Angle Chisel 40mm	200



SDS MAX Chisels

Product Code	Description/Dimensions (mm)	Overall Length (mm)
TMPC18280	Pointed Ø18x280	280
TMPC18400	Pointed Ø18x400	400
TMFC24280	Flat Chisel 24mm	280
TMFC24400	Flat Chisel 24mm	400
TMFC50360	Flat Chisel 50mm	360
TMFC80300	Flat Chisel 80mm	300
TMFC115350	Flat Chisel 115mm	350
TCMC26300	Concrete Chasing Chisel 26mm	300
TMAB50300	Flat Chisel Crouched 50mm	300
THBH1645	Bush Hammer Head	280

SDS + Stop Drop in drill bits



Product Code	Description	Box Packing
TCPD1033	M10 x 33 SDS+ Drill bit STOP	1
TCPD1243	M12 x 43 SDS+ Drill bit STOP	1
TCPD1552	M15 x 53 SDS+ Drill bit STOP	1



Flat Ultra-Thin Abrasive Wheels for Cutting of Steel

Product Code	Disc Dimensions D x H x d [mm]	Maximum Operating Speed (rev/min)	Colour label	Box Packing	Weight (kg/pcs)
TAMF125/1.0C	125x1.0x22.2	12200	Blue	25	0,03
TAMF125/1.6C	125x1.6x22.2	12200	Blue	25	0,04
TAMF230/2.0C	230x2.0x22.2	6600	Blue	25	0,183



ABRASIVE DISCS

Flat Abrasive Wheels for Cutting of Stainless and Acid Resistant Steel, INOX

Product Code	Disc Dimensions D x H x d [mm]	Maximum Operating Speed (rev/min)	Colour label	Box Packing	Weight (kg/pcs)
TSSF125/1.0CMM	125x1.0x22.2	12200	Silver	25	0,03
TSSF230/2.0CMM	230x2.0x22.2	6600	Silver	25	0,186




Depressed-Centre Abrasive Wheels for Grinding Steel

Product Code	Disc Dimensions D x H x d [mm]	Maximum Operating Speed (rev/min)	Colour label	Box Packing	Weight (kg/pcs)
TAMDC125/6.0G	125x6.0x22.2	12200	Red	10	0,162



Diamond Cutting Discs

Product Code	Product Type	Dimensions mm	Packaging
TDDL125	Laser 125mm	125/22,5	1
TDDL230	Laser 230mm	230/22,5	1
TDDT125	Turbo 125mm	125/22,5	1
TDDT230	Turbo 230mm	230/22,5	1



AVAILABLE VIA DIRECT SHIPMENT FROM OUR ASIAN FACTORIES

MOQ Pallet Quantities - Full Container Order

Drywall Screw - Coarse Thread (Black Phosphate)

Product Code	Screw Diameter (mm)	Screw Length (mm)	Head Type	Box Packing	Outer Packing	Pallet Packing
TDWS35025C	3.5	25	PH2	1000	5000	300000
TDWS35032C	3.5	32	PH2	1000	5000	300000
TDWS35035C	3.5	35	PH2	1000	5000	300000
TDWS35038C	3.5	38	PH2	1000	5000	300000
TDWS35045C	3.5	45	PH2	1000	5000	300000
TDWS35050C	3.5	50	PH2	1000	5000	300000
TDWS35055C	3.5	55	PH2	500	2500	150000
TDWS35060C	3.5	60	PH2	500	2500	150000
TDWS42065C	4.2	65	PH2	500	2500	150000
TDWS42075C	4.2	75	PH2	500	2500	150000
TDWS48100C	4.8	100	PH2	250	1250	75000

Drywall Screw - Fine Thread (Black Phosphate)

Product Code	Screw Diameter (mm)	Screw Length (mm)	Head Type	Box Packing	Outer Packing	Pallet Packing
TDWS35025F	3.5	25	PH2	1000	5000	300000
TDWS35032F	3.5	32	PH2	1000	5000	300000
TDWS35035F	3.5	35	PH2	1000	5000	300000
TDWS35038F	3.5	38	PH2	1000	5000	300000
TDWS35045F	3.5	45	PH2	1000	5000	300000
TDWS35050F	3.5	50	PH2	1000	5000	300000
TDWS35055F	3.5	55	PH2	500	2500	150000
TDWS35060F	3.5	60	PH2	500	2500	150000
TDWS42065F	4.2	65	PH2	500	2500	150000
TDWS42075F	4.2	75	PH2	500	2500	150000
TDWS48100F	4.8	100	PH2	250	1250	75000

Drywall Screw - Collated Coarse Thread (Black Phosphate)

Product Code	Screw Diameter (mm)	Screw Length (mm)	Head Type	Box Packing	Outer Packing	Pallet Packing
TDWS35025S	3.5	25	PH2	1000	10000	180000
TDWS35032S	3.5	32	PH2	1000	10000	180000
TDWS35035S	3.5	35	PH2	1000	10000	180000
TDWS35038S	3.5	38	PH2	1000	10000	180000
TDWS35045S	3.5	45	PH2	1000	6000	108000
TDWS35050S	3.5	50	PH2	1000	6000	108000
TDWS35055S	3.5	55	PH2	1000	6000	108000
TDWS35060S	3.5	60	PH2	1000	6000	108000
TDWS42065S	4.2	65	PH2	1000	4000	72000

Metal Framing Screw - Standard Profile (Steel White Zinc Plated)

Product Code	Screw Diameter (mm)	Screw Length (mm)	Head Type	Box Packing	Outer Packing	Pallet Packing
TMFS35025	3.5	25	PH2	1000	5000	300000
TMFS42025	4.2	25	PH2	1000	5000	300000
TMFS35016	3.5	16	PH2	1000	5000	300000
TMFS42013	4.2	13	PH2	1000	5000	300000
TMFS42019	4.2	19	PH2	1000	5000	300000
TMFS39011	3.9	11	PH2	1000	5000	300000



AVAILABLE VIA DIRECT SHIPMENT FROM OUR ASIAN FACTORIES

MOQ Pallet Quantities - Full Container Order

Drywall Screw - Self Tapping (Steel White Zinc Plated)

Product Code	Screw Diameter (mm)	Screw Length (mm)	Head Type	Box Packing	Outer Packing	Pallet Packing
TDWS35025ST	3.5	25	PH2	1000	5000	300000
TDWS35032ST	3.5	32	PH2	1000	5000	300000
TDWS35035ST	3.5	35	PH2	1000	5000	300000
TDWS35038ST	3.5	38	PH2	1000	5000	300000
TDWS35045ST	3.5	45	PH2	1000	5000	300000
TDWS35050ST	3.5	50	PH2	1000	5000	300000
TDWS35055ST	3.5	55	PH2	500	2500	150000
TDWS35060ST	3.5	60	PH2	500	2500	150000
TDWS42065ST	4.2	65	PH2	500	2500	150000
TDWS42075ST	4.2	75	PH2	500	2500	150000
TDWS48100ST	4.8	100	PH2	250	1250	75000



DRYWALL SCREWS

Drywall Screw - Fine Thread (Steel White Zinc Plated)

Product Code	Screw Diameter (mm)	Screw Length (mm)	Head Type	Box Packing	Outer Packing	Pallet Packing
TDWS35025FZ	3.5	25	PH2	1000	5000	300000
TDWS35032FZ	3.5	32	PH2	1000	5000	300000
TDWS35035FZ	3.5	35	PH2	1000	5000	300000
TDWS35038FZ	3.5	38	PH2	1000	5000	300000
TDWS35045FZ	3.5	45	PH2	1000	5000	300000
TDWS35050FZ	3.5	50	PH2	1000	5000	300000
TDWS35055FZ	3.5	55	PH2	500	2500	150000
TDWS35060FZ	3.5	60	PH2	500	2500	150000
TDWS42065FZ	4.2	65	PH2	500	2500	150000
TDWS42075FZ	4.2	75	PH2	500	2500	150000
TDWS48100FZ	4.8	100	PH2	250	1250	75000



Drywall Screw - Collated Fine Thread (Steel White Zinc Plated)

Product Code	Screw Diameter (mm)	Screw Length (mm)	Head Type	Box Packing	Outer Packing	Pallet Packing
TDWS35025SZ	3.5	25	PH2	1000	10000	180000
TDWS35032SZ	3.5	32	PH2	1000	10000	180000
TDWS35035SZ	3.5	35	PH2	1000	10000	180000
TDWS35038SZ	3.5	38	PH2	1000	10000	180000
TDWS35045SZ	3.5	45	PH2	1000	6000	108000
TDWS35050SZ	3.5	50	PH2	1000	6000	108000
TDWS35055SZ	3.5	55	PH2	1000	6000	108000
TDWS35060SZ	3.5	60	PH2	1000	6000	108000
TDWS42065SZ	4.2	65	PH2	1000	4000	72000



Metal Framing Screw - Wafer Head (Steel White Zinc Plated)

Product Code	Screw Diameter (mm)	Screw Length (mm)	Point Type	Head Type	Box Packing	Outer Packing	Pallet Packing
TMFS42013W	4.2	13	Self-Drilling	PH2	1000	5000	300000
TMFS42016W	4.2	16	Self-Drilling	PH2	1000	5000	300000
TMFS42019W	4.2	19	Self-Drilling	PH2	1000	5000	300000
TMFS42025W	4.2	25	Self-Drilling	PH2	1000	5000	300000
TMFS42013WS	4.2	13	Sharp	PH2	1000	5000	300000



SOLAR PANEL FIXINGS

Double Threaded Bolt Kit - A2 Stainless

Product Code	Hole Diameter (mm)	Anchor Length (mm)	Socket Wrench	Nut	Box Packing	Outer Packing
TDTB10250	10	250	SW7	DIN -6923 x 3	25	200

Self Tapping Screw Kit - A2 Stainless

Product Code	Hole Diameter (mm)	Anchor Length (mm)	Socket Wrench	Nut	Box Packing	Outer Packing
TSTSK10160	10	160	SW5	DIN - 985 & 934	25	200
TSTSK10200	10	200	SW5	DIN - 985 & 934	25	200

Adaptor Plates - A2 Stainless

Product Code	Size	Anchor Length (mm)	Anchor Width (mm)	Hole Size (mm)	Box Packing	Outer Packing
TPVAP10	M10	82	30	11 x 29.5	50	1000
TPVAP12	M12	82	30	11 x 29.5	50	1000

Plate Size (mm)

Roof Hook (universal) - A2 Stainless

Product Code	Hook Size (mm)		Adjustable Height (mm)	Use With Bolt	Box Packing	Outer Packing
TPVRH30	30x5	140x56x5	40-55	M8	25	500

Round Head Screw DIN-603 - A2 Stainless

Product Code	Anchor Diameter (mm)	Anchor Length (mm)	Head Diameter (mm)	DIN	Box Packing	Outer Packing
TDIN603816	8	16	20	DIN - 603	50	1000

Cross Connector - A2 Stainless

Product Code	Anchor Diameter (mm)	Anchor Length (mm)	Connector Length (mm)	DIN	Box Packing	Outer Packing
TPVCCM8	8	20	23	DIN - 6923 M8	50	1000



DIN 6921 - A2 Stainless

Product Code	Anchor Diameter (mm)	Anchor Length (mm)	Washer Diameter (mm)	DIN	Box Packing	Outer Packing
THFD0820	8	20	23	DIN - 6921 M8	50	1000
THFD0850	8	50	23	DIN - 6921 M8	50	1000
THFD0870	8	70	23	DIN - 6921 M8	50	1000



NEW

SOLAR PANEL FIXINGS

Thin Sheet Screw A2 EPDM Washer

Product Code	Anchor Diameter (mm)	Anchor Length (mm)	Washer Diameter (mm)	Socket Wrench	Box Packing	Outer Packing
TPVTSS5516	5.5	25	16	Sw8	100	2000



NEW

Bi - Metal Thin Sheet Screw - A2 Stainless EPDM Washer

Product Code	Anchor Diameter (mm)	Anchor Length (mm)	Washer Diameter (mm)	Socket Wrench	Box Packing	Outer Packing
TPVTSS0616SS	6	25	16	Sw8	100	2000



NEW

Self Drilling Screw A2 EPDM Washer

Product Code	Anchor Diameter (mm)	Anchor Length (mm)	Washer Diameter (mm)	Socket Wrench	Box Packing	Outer Packing
TPVTSS5516	6	25	16	Sw8	100	2000



NEW

Bi - Metal Self Drilling Screw - A2 Stainless A2 EPDM Washer

Product Code	Anchor Diameter (mm)	Anchor Length (mm)	Washer Diameter (mm)	Socket Wrench	Box Packing	Outer Packing
TPVTSS5516	6	25	16	Sw8	100	2000



NEW

TESTING EQUIPMENT

KT-6 Tester Kit



To easily verify the strength of post-installed anchor bolts on site, we have designed and developed the AT Series of non-destruction testing machines, which can fit various tests required for installing equipment, earthquake resistance, civil engineering work or other applications.

Easy maneuverability and simple fun equipment.

or managing on-site building

FEATURES:

- Light-weight, compact design applicable to various on-site tests
- Easy operation enables tension testing up to 6kn
- Measure and save tension and displacement value digitally
- Improve work efficiency significantly
- Power cord free

M2000 Pro Tester Kit



The Hydrajaws M2000 PRO Tester Kit anchor tester contains a universal set of adaptors enabling a comprehensive range of fixings and safety-critical applications, up to a maximum tensile load of 25kN (5620lbf) to be tested. Trusted by market-leading companies worldwide, the M2000 PRO Tester Kit anchor tester is an essential tool for carrying out testing procedures in line with BS 8539, BS 7883, and BS EN 795.

The M2000 PRO Tester Kit is easy to use and easily transported. It comes complete with a comprehensive full-colour user manual and backing and support from our technical team at Hydrajaws.

FEATURES:

- 0-25kN Dual Scale digital gauge compatible with the latest Hydrajaws App (detachable for calibration, reduces carrier return costs).
- 2020 Load spreading bridge featuring height adjustable legs with pin arrangement in four positions with swivel feet giving 15mm of fine adjustment.
- Turning Handle with 22mm (7/8") integrated nut (for use in confined spaces).
- Up to 50mm of stroke.
- The anchor tester is preassembled and accessories can be quickly attached with ease.
- Hydrajaws gauge calibration certificate (valid for 12 months).
- Supplied in a robust protective carry case with full operating instructions.

M2000 Scaffold Tie Tester Kit



The Hydrajaws M2000 Scaffold Tie Tester Kit is a specific kit allowing Scaffolders to test all common scaffold anchors and fixings in general use today in line with NASC Guidance Note TG4:19. Manufactured to exacting high standards, the kit contains adaptors to test the most commonly used anchors used for scaffold ties up to a maximum tensile load of 25kN (5620lbf).

The three-legged load spreading bridge keeps reaction loads away from the fixing allowing results to be more consistent. Trusted by the best scaffolding companies in the world, the M2000 Scaffold Tie Tester Kit is an essential tool for any scaffolder wanting to comply with current health and safety practices.

FEATURES:

- 0-25kN Dual Scale digital gauge compatible with the latest Hydrajaws App (detachable for calibration, reduces carrier return costs)
- 2020 Load spreading bridge featuring height adjustable legs with pin arrangement in four positions with swivel feet giving 15mm of fine adjustment.
- Turning Handle with 22mm (7/8") integrated nut (for use in confined spaces)
- Up to 50mm of stroke
- The tester is preassembled and accessories can be quickly attached with ease
- Hydrajaws gauge calibration certificate (valid for 12 months)
- Supplied in a robust protective carry case with full operating instructions.



M2050 Medium Heavy Tester Kit

Extending the testing range to cover 0-50kN, the Hydrajaws M2050 PRO Tester Kit enables engineers to validate the correct installation or establish the safe working loads of a comprehensive range of anchors & fixings in line with BS 8539 up to a maximum tensile load of 50kN (11240lbf).

Manufactured to exacting high standards, the Hydrajaws M2050 PRO Tester kit contains a universal set of adaptors allowing a wide range of anchors and fixings used in safety-critical applications to be tested. The three-legged load spreading bridge keeps reaction loads away from the fixing allowing results to be more consistent.

FEATURES:

- 0-50kN Dual Scale digital gauge compatible with the latest Hydrajaws App (detachable for calibration, reduces carrier return costs)
- 2050 Load spreading bridge featuring height adjustable legs with pin arrangement in six positions with swivel feet giving 30mm of fine adjustment.
- Turning Handle with 24mm integrated nut (for use in confined spaces)
- Up to 50mm of stroke
- The tester is preassembled and accessories can be quickly attached with ease
- Hydrajaws gauge calibration certificate (valid for 12 months)
- Supplied in a robust protective carry case with full operating instructions.



TESTING EQUIPMENT

M2008 Heavy Duty Tester Kit

The portable self-contained M2008 Heavy Duty Tester meets the demand for proof load testing larger fixings up to 145kN (32597lbf). Applications include high load expanding and resin anchors, holding down bolts for stanchion base plates, base plate fixings for column lighting, anchorage for crash barrier and safety fences, anchorage for stadium crush barriers and bridge parapet anchors.

With optional extras, applications include rebar pull-out test, pad eye load test, large ringbolt, and eyebolt testing. Having a lightweight aluminium height adjustable load spreading bridge means the weight combined with the tester is only 14kg, which is lighter and more convenient to apply than a separate hydraulic pump and arrangement.

FEATURES:

- 0-145kN Dual Scale Digital Gauge compatible with the latest Hydrajaws App (detachable for calibration, reduces carrier return costs).
- 2008 lightweight aluminium off set triangular load-spreading bridge with nine height positions. The swivel feet offer fine height adjustment.
- Load application achieved via a 24mm ratchet handle driving a hydraulic multiplier.
- Spirit level to indicate the overall balance of the test rig.
- 10mm eyehook installed for attaching a lanyard as appropriate.
- The foam filler can accommodate four rebar adaptors.
- Hydrajaws gauge calibration certificate (valid for 12 months).
- Supplied in a wheeled robust carry case with telescopic handle and full operating instructions.



Kits Include below, other accessories available also.



TRUTEK - IPT GENERATION X 21700 CELL TECHNOLOGY



**TWICE
THE POWER
TWICE THE
PERFORMANCE**

TRUTEK - IPT JOINT VENTURE DEVELOPING
NEW RANGE OF HIGH PERFORMANCE
BATTERIES IN 20V, 40V, & 58V.



Take our old battery (18650) , for example. Our standard 20V batteries can produce up to 800 watts of power output. When we upgraded to Generation X, it went up to 1440 watts—an 80% power increase!

It gives us the ability to produce cordless tools that we didn't think we'd ever see without a cord just a few years ago. And many of them are outperforming their corded counterparts now.

Power tools are hardly the end product, we plan to offer outdoor power equipment for lawn care and landscaping, battery-powered inverters, and high-powered construction equipment are all starting to have cordless options thanks to 21700 lithium-ion battery cells.



NEW

TRUTEK / IPT POWER TOOLS

Industrial Power Tools (IPT) was created in 2015 to produce high quality battery tools; with production facilities set up in China & South Korea. In 2020 IPT made a joint venture agreement together with Osung of Korea to produce the next generation 21700 battery cells. All IPT tools today will be supplied with batteries and chargers from Korea, produced & supplied by Osung with Samsung cells. Development is ongoing with plans to add 40v & 58v tools. As you can see from below, Trutek / IPT offers a wide range for all your construction site needs. From drilling to grinding to other job-site necessities such as LED lights, fans and radios. the range is ever expanding!



TRUTEK BRANDING

BRANDING



Trutek offers a wide range of POS material to maximise branding and potential sales, wherever the requirement. A complete SOLUTION.

HIGH END PACKAGING


Trutek's new branded packaging emphasises the quality and reliability of its products. Strong presence and clear product selection is the RESULT.







TRUTEKTM
CONSTRUCTION FASTENING SYSTEMS



HEAD OFFICE

Trutek Fastening Systems UK Ltd
Unit 6, New Hall Hey Industrial Estate
New Hall Hey Road
Rawtenstall
Lancashire
BB4 6HL
United Kingdom

Email: Sales@trutekfixings.co.uk

tel: +44 (0) 1706 614105

www.trutekfasteners.eu

